

SAFETY DATA SHEET



n-Heptane (Pure Grade)

Version 1.9

Revision Date 2021-08-12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product information

Product Name : n-Heptane (Pure Grade)
Material : 1119723, 1099971, 1016082, 1099970, 1084145, 1061726,
1021845, 1028621, 1021842, 1021844, 1028384, 1028355,
1021843, 10455211

Company : Epic Chemical Solutions, Inc.
P.O. Box 761403
San Antonio, TX 78245

Emergency telephone: 855-791-9900

Transport:
INFOTRAC 800-535-5053

E-mail address : Info@EpicChemicalSolutions.com
Website : www.EpicChemicalSolutions.com

SECTION 2: Hazards identification

Classification of the substance or mixture
GHS Classification and labelling according to JIS Z 7252-2019 and JIS Z 7253-2019 (GHS 2015)

Classification

: Flammable liquids, Category 2
Skin corrosion/irritation, Category 2
Serious eye damage/eye irritation, Category 2
Specific target organ toxicity - single exposure, Category 3,

n-Heptane (Pure Grade)

Version 1.9

Revision Date 2021-08-12

Respiratory tract irritation, Narcotic effects
 Specific target organ toxicity - repeated exposure, Category 1,
 Nervous system
 Aspiration hazard, Category 1
 Short-term (acute) aquatic hazard, Category 1
 Long-term (chronic) aquatic hazard, Category 1

Labeling

Symbol(s)



Signal Word

: Danger

Hazard Statements

: H225: Highly flammable liquid and vapor.
 H304: May be fatal if swallowed and enters airways.
 H315: Causes skin irritation.
 H319: Causes serious eye irritation.
 H335: May cause respiratory irritation.
 H336: May cause drowsiness or dizziness.
 H372: Causes damage to organs (Nervous system) through prolonged or repeated exposure.
 H410: Very toxic to aquatic life with long lasting effects.

Precautionary Statements

: **Prevention:**
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P233 Keep container tightly closed.
 P240 Ground and bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
 P242 Use non-sparking tools.
 P243 Take action to prevent static discharges.
 P260 Do not breathe dust/fume/gas/mist/vapor/spray.
 P264 Wash skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P271 Use only outdoors or in a well-ventilated area.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ eye protection/ face protection.
Response:
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.
 P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P314 Get medical advice/ attention if you feel unwell.
 P331 Do NOT induce vomiting.
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P362 + P364 Take off contaminated clothing and wash it

n-Heptane (Pure Grade)

Version 1.9

Revision Date 2021-08-12

before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

SECTION 3: Composition/information on ingredients

Synonyms : Normal Heptane
Dipropilmetano
n-Heptane, 99%

Molecular formula : C7H16

Chemical name	CAS-No.	Concentration	ENCS/ISHL number
n-Heptane	142-82-5	100%	2-7 2-7

SECTION 4: First aid measures

General advice : Move out of dangerous area. Show this material safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later. Do not leave the victim unattended.

If inhaled : Move to fresh air. If unconscious, place in recovery position and seek medical advice. If symptoms persist, call a physician.

In case of skin contact : If skin irritation persists, call a physician. If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Take victim immediately to hospital.

SECTION 5: Firefighting measures

Flash point : -4°C (25°F)
Method: Tag closed cup

n-Heptane (Pure Grade)

Version 1.9

Revision Date 2021-08-12

Autoignition temperature	: 203.85°C (398.93°F)
Suitable extinguishing media	: Dry chemical. Carbon dioxide (CO ₂). Alcohol-resistant foam.
Unsuitable extinguishing media	: High volume water jet.
Specific hazards during fire fighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Special protective equipment for fire-fighters	: Wear self-contained breathing apparatus for firefighting if necessary.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containment. Use a water spray to cool fully closed containers.
Fire and explosion protection	: Do not spray on an open flame or any other incandescent material. Use only explosion-proof equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.
Hazardous decomposition products	: Carbon oxides.

SECTION 6: Accidental release measures

Personal precautions	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods for cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7: Handling and storage**Handling**

Advice on safe handling	: Avoid formation of aerosol. Do not breathe vapors/dust. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Provide sufficient air exchange and/or
-------------------------	---

SDS Number:10000067062

4/14

n-Heptane (Pure Grade)

Version 1.9

Revision Date 2021-08-12

exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.

Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary, but may not by themselves be sufficient. Review all operations, which have the potential to generating and accumulation of electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures. For more information, refer to OSHA Standard 29 CFR 1910.106 "Flammable and Combustible Liquids"; National Fire Protection Association (NFPA 77), "Recommended Practice on Static Electricity"; and/or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising Out of Static, Lightning, and stray Currents".

Advice on protection against fire and explosion : Do not spray on an open flame or any other incandescent material. Use only explosion-proof equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from open flames, hot surfaces and sources of ignition.

Storage

Requirements for storage areas and containers : No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8: Exposure controls/personal protection**Ingredients with workplace control parameters**

JP

Components	Basis	Value	Control parameters	Note
n-Heptane	JP OEL JSOH	OEL-M	200 ppm, 820 mg/m ³	

Engineering measures

Adequate ventilation to control airborne concentrations below the exposure guidelines/limits. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection : Wear a supplied-air NIOSH approved respirator unless ventilation or other engineering controls are adequate to maintain minimal oxygen content of 19.5% by volume under normal atmospheric pressure. Wear a NIOSH approved respirator that provides protection when working with this

n-Heptane (Pure Grade)

Version 1.9

Revision Date 2021-08-12

	material if exposure to harmful levels of airborne material may occur, such as: Air-Purifying Respirator for Organic Vapors. Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection.
Hand protection	: The suitability for a specific workplace should be discussed with the producers of the protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.
Eye protection	: Eye wash bottle with pure water. Lightly fitting safety goggles.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place. Wear as appropriate: Flame retardant antistatic protective clothing. Workers should wear antistatic footwear.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

Form	: Liquid
Physical state	: Liquid
Color	: Clear
Odor	: Sweet

Safety data

Flash point	: -4°C (25°F) Method: Tag closed cup
Lower explosion limit	: 1 %(V)
Upper explosion limit	: 7 %(V)
Oxidizing properties	: no
Autoignition temperature	: 203.85°C (398.93°F)
Molecular formula	: C7H16
Molecular weight	: 100.23 g/mol
pH	: Not applicable
Pour point	: No data available

n-Heptane (Pure Grade)

Version 1.9

Revision Date 2021-08-12

Boiling point/boiling range	: 98°C (208°F)
Vapor pressure	: 1.60 PSI at 38°C (100°F)
Relative density	: 0.69 at 16 °C (61 °F)
Density	: 5.75 L/G at 20°C (68°F)
Water solubility	: Negligible
Partition coefficient: n-octanol/water	: No data available
Relative vapor density	: 3.4 (Air = 1.0)
Evaporation rate	: 3.46
Percent volatile	: > 99 %
Conductivity	: < 1 pSm at 20 °C

SECTION 10: Stability and reactivity

Chemical stability	: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Possibility of hazardous reactions	
Hazardous reactions	: Hazardous reactions. Hazardous polymerization does not occur. Further information. No decomposition if stored and applied as directed. Hazardous reactions. Vapors may form explosive mixture with air.
Conditions to avoid	: Not applicable.
Materials to avoid	: May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
Hazardous decomposition products	: Oxidizing solids. Oxidizing liquids. Carbon oxides
Other data	: No decomposition if stored and applied as directed.

n-Heptane (Pure Grade)

Version 1.9

Revision Date 2021-08-12

SECTION 11: Toxicological information**Acute oral toxicity**

n-Heptane : LD50: > 5,000 mg/kg
Species: Rat
Method: OECD Test Guideline 401
Information given is based on data obtained from similar substances.

Acute inhalation toxicity

n-Heptane : LC50: > 29.29 mg/l
Exposure time: 4 h
Species: Rat
Sex: male and female
Test atmosphere: vapor
Method: OECD Test Guideline 403

Acute dermal toxicity

n-Heptane : LD50: > 2,000 mg/kg
Species: Rabbit
Sex: male and female
Method: OECD Test Guideline 402
Information given is based on data obtained from similar substances.

**n-Heptane (Pure Grade)
Skin irritation**

: Irritating to skin.
May cause skin irritation in susceptible persons.

**n-Heptane (Pure Grade)
Eye irritation**

: Vapors may cause irritation to the eyes, respiratory system and the skin.

Sensitization

n-Heptane : Did not cause sensitization on laboratory animals.
Information given is based on data obtained from similar substances.

Repeated dose toxicity

n-Heptane : Species: Rat, male
Sex: male
Application Route: Inhalation
Dose: 12.47 mg/l
Exposure time: 16 wk
Number of exposures: 12 h/d, 7 d/wk
NOEL: 12.47 mg/l
No adverse effect has been observed in chronic toxicity tests.

n-Heptane (Pure Grade)

Version 1.9

Revision Date 2021-08-12

Species: Rat, Male and female
 Sex: Male and female
 Application Route: Inhalation
 Dose: 12.35 mg/l
 Exposure time: 26 wk
 Number of exposures: 6 h/d, 5 d/wk
 Method: OECD Test Guideline 413
 No adverse effect has been observed in chronic toxicity tests.

Genotoxicity in vitro

n-Heptane

: Test Type: Ames test
 Method: Mutagenicity (Escherichia coli - reverse mutation assay)
 Result: negative

Test Type: Mammalian cell gene mutation assay
 Method: OECD Guideline 476
 Result: negative

Test Type: Chromosome aberration test in vitro
 Method: OECD Guideline 473
 Result: negative

Test Type: Mitotic recombination
 Result: negative

Reproductive toxicity

n-Heptane

: Species: Rat
 Sex: male and female
 Application Route: Inhalation
 Dose: 0, 900, 3000, 9000 ppm
 Number of exposures: 6 hr/d, 5 d/wk
 Test period: 13 wk
 Method: OECD Test Guideline 416
 NOAEL Parent: 9000 ppm
 NOAEL F1: 3000 ppm
 NOAEL F2: 3000 ppm
 Information given is based on data obtained from similar substances.

Developmental Toxicity

n-Heptane

: Species: Rat
 Application Route: Inhalation
 Dose: 0, 900, 3000, 9000 ppm
 Exposure time: GD6-15
 Number of exposures: 6 hrs/d
 NOAEL Teratogenicity: 9000 ppm
 NOAEL Maternal: 3000 ppm

**n-Heptane (Pure Grade)
Aspiration toxicity**

: May be fatal if swallowed and enters airways.
 Substances known to cause human aspiration toxicity hazards or to be regarded as if they cause human aspiration toxicity hazard.

n-Heptane (Pure Grade)

Version 1.9

Revision Date 2021-08-12

CMR effects

n-Heptane : Mutagenicity: Tests on bacterial or mammalian cell cultures did not show mutagenic effects.
 Teratogenicity: Animal testing did not show any effects on fetal development.
 Reproductive toxicity: No toxicity to reproduction

**n-Heptane (Pure Grade)
Further information**

: Concentrations substantially above the TLV value may cause narcotic effects. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
 Solvents may degrease the skin.

SECTION 12: Ecological information**Toxicity to fish**

n-Heptane : LL50: 5.738 mg/l
 Exposure time: 96 h
 Species: *Oncorhynchus mykiss* (rainbow trout)
 Method: QSAR modeled data

Toxicity to daphnia and other aquatic invertebrates

n-Heptane : EC50: 1.5 mg/l
 Exposure time: 48 h
 Species: *Daphnia magna* (Water flea)
 static test Toxic to aquatic organisms.

LC50: 0.1 mg/l
 Exposure time: 96 h
 Species: *Mysidopsis bahia* (mysid shrimp)
 semi-static test Very toxic to aquatic organisms.

Toxicity to algae

n-Heptane : EL50: 4.338 mg/l
 Exposure time: 72 h
 Species: *Pseudokirchneriella subcapitata* (microalgae)
 Method: QSAR

Toxicity to fish (Chronic toxicity)

n-Heptane : NOELR: 1.284 mg/l
 Exposure time: 28 d
 Species: *Oncorhynchus mykiss* (rainbow trout)
 Method: QSAR modeled data

Biodegradability

n-Heptane (Pure Grade)

Version 1.9

Revision Date 2021-08-12

n-Heptane	: Result: Readily biodegradable. 70 % Testing period: 10 d
Results of PBT assessment n-Heptane	: Non-classified PBT substance, Non-classified vPvB substance
Additional ecological information	: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Very toxic to aquatic life with long lasting effects.
Ecotoxicology Assessment	
Short-term (acute) aquatic hazard n-Heptane	: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard n-Heptane	: Very toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product	: The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)
UN1206, HEPTANES, 3, II, MARINE POLLUTANT, (HEPTANE)

n-Heptane (Pure Grade)

Version 1.9

Revision Date 2021-08-12

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)
UN1206, HEPTANES, 3, II, (-4°C), MARINE POLLUTANT, (HEPTANE)

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)
UN1206, HEPTANES, 3, II

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))
UN1206, HEPTANES, 3, II, (D/E), ENVIRONMENTALLY HAZARDOUS, (HEPTANE)

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))
UN1206, HEPTANES, 3, II, ENVIRONMENTALLY HAZARDOUS, (HEPTANE)

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)
UN1206, HEPTANES, 3, II, ENVIRONMENTALLY HAZARDOUS, (HEPTANE)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information**National legislation****Poisonous and Deleterious Substances Control Law**

: Not relevant

Industrial Safety and Health Law

Substances Subject to be : heptane(526)
Notified Names

Enforcement Order of the : Inflammable Substance
Industrial Safety and Health
Law - Attached table 1
(Dangerous Substances)

Hazardous Substances : Not relevant
Subject to Labeling
Requirements

Ordinance on Prevention of : Not relevant
Organic Solvent Poisoning

Chemical Substance Control Law

: Not relevant

n-Heptane (Pure Grade)

Version 1.9

Revision Date 2021-08-12

Act on Confirmation, etc. of Release Amounts of Specific Chemical Substances in the Environment and Promotion of Improvements to the Management Thereof

: Not relevant

Other regulations

Fire Service Law : Flammable liquids
Type 1 petroleum
Hazardous rank II

Notification status

Europe REACH : This product is in full compliance according to REACH regulation 1907/2006/EC.

Switzerland CH INV : On the inventory, or in compliance with the inventory

United States of America (USA) TSCA : On or in compliance with the active portion of the TSCA inventory

Canada DSL : All components of this product are on the Canadian DSL

Australia AICS : On the inventory, or in compliance with the inventory

New Zealand NZIoC : On the inventory, or in compliance with the inventory

Japan ENCS : On the inventory, or in compliance with the inventory

Korea KECI : All substances in this product were registered, notified to be registered, or exempted from registration by CPChem through an Only Representative according to K-REACH regulations. Importation of this product is permitted if the Korean Importer of Record was included on CPChem's notifications or if the Importer of Record themselves notified the substances.

Philippines PICCS : On the inventory, or in compliance with the inventory

China IECSC : On the inventory, or in compliance with the inventory

Taiwan TCSI : On the inventory, or in compliance with the inventory

SECTION 16: Other information**Further information**

Legacy SDS Number : 133

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level

n-Heptane (Pure Grade)

Version 1.9

Revision Date 2021-08-12

DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		